



AIS 140 GPS

Multifunctional Vehicle GPS Tracker



Real-time GPS+AGPS tracking

Allow the location to be pinpointed in real time or periodically



IP66 dust and water proof

Water-resistant to ensure stable operation in tough environment



Maximum 50000 data logs

Memorize a large amount of gps data when device enters GSM blind zone



Door status detection

Get instant alert when your car's door is open unexpectedly



SOS emergency call

In case of emergency,press the SOS button to trigger an urgent call



Two-way communication

With MIC and speaker, it's easy to realize voice-monitor or two-way audio



Multiple analog & digital I/O

Monitor and control external application via input/outputs



Multiple alarms

Instant alert for vibration, overspeed, power off, geo-fence

Application



Fleet management



Vehicle tracking



Taxi



Sppedtrackgps

Geniune service 4ever

GSM Specification

GSM frequency	850/900/1800/1900 MHz
GPRS	Class 12, TCP/IP
Memory	64 Mb
Phase error	RMSPE<5,PPE<20
Max output	GSM850/GSM900:33±3dBm GSM1800/GSM1900:30±3dBm
Max frequency error	±0.1ppm

GPS Specification

GPS chipset	MTK high sensitivity chip
Frequency	L1,1575.42MHz C/A code
GPS channel	66
Location accuracy	<10 meters
Tracking sensitivity	-162dBm
Acquisition sensitivity	-148dBm
TTF (open sky)	Avg. hot start ≤1sec Avg. cold start ≤32sec

Function & Package

Voice monitor range	≤5 meters
Battery	800mAh/3.7V Li-Polymer battery
Working voltage/current	9-36VDC/45mA(12VDC), 28mA(24VDC)
Operating temperature	-20°C~ 70°C
Device weight	91.7g
Device dimension	93.0(L)*76.0(W)*18.0(H)mm
Box weight	615.5g
Box dimension	211(L)*148(W)*66(H)mm
Accessories	Power cable, SOS cable, Microphone, Relay(4pin), 2*Relay(5pin), Speaker, I&O cable

Contact

1105 Royel Palm Goregaon East Mumbai
 Call: +91 7834827001 , 7701934388
 Write Us: info@sppedtrackgps.in
 Web: <https://sppedtrackgps.in>